

**Serie - series - série 48**



Serie-series-série	Nennweite-diameter-diamètre	Manschettenqualität - sleeve quality - qualité de manchon								
48	65. (DN 65, G 2½")	NR	NR-L	NR-LH	NBR-LH	EPDM-L	FPM	CR	CSM	Standard
		001.	011.	021.	121.	211.	301.	401.	501.	000
		<b>ATEX Version</b>		NR-E	NR-LE	NBR-LE	EPDM-LE	000		
			031.	061.	161.	261.				

L = FDA-konform - in compliance with FDA - conforme à FDA      H = hell (weiss) - pale (white) - clair (blanc)  
 E = ATEX-konform - in compliance with ATEX - conforme à ATEX

**Manschette - sleeve - manchon**  
 nach Wahl (siehe Tabelle oben)  
 as selected (see table above)  
 au choix (voir tableau ci-dessus)  
 example: 4065.xxx.x00

**Sicherungsstift - locking pin - cheville d'arrêt**  
 art.no. 4065.08    2.5 x 20 mm

**O-Ring - o-ring - joint torique**  
 NBR / 2x  
 art.no. 4065.06    102 x 4 mm

**Schrauben - screws - vis**  
 M8 x 18 mm  
 art.no. 4865.07    12x

